



PRODUCT DATA SHEET

ANDEROL PQAA 150

H1 Food Grade Gear Lubricant



ADVANTAGES/BENEFITS

- Product was developed with highly stable white oil
- Product has excellent wear and load carrying capacity
- Rust and oxidation inhibited
- Good water separation

COMPATIBILITY

ANDEROL® highly refined oil based lubricants are similar to mineral oils in their compatibility with paints, seals, gaskets and hoses. No special precautions related to compatibility are required when changing over from a mineral oil lubricant to this product.

APPLICATION

H1 Food Approved gear lubricant suitable for food manufacturing applications where incidental food contact may occur.

Recommended for use in:

- Bearings and gears
- Chain lubrication
- Wipe down oil
- Worm gear applications

Can generally be used in all other rotating equipment applications where incidental food contact may occur.

APPROVALS

- Unilever

ANDEROL PQAA 150 is a white oil based H1 registered lubricant, combined with high performance additives. They are designed to provide outstanding lubrication protection to gear sets, bearings and pumps in applications in the food industry.

Anderol PQAA range is available in the grades ISO VG 150, 220, 320, 460, 680 & 1000.

ANDEROL PQAA 150 is NSF/H1 registered. The product is certified Kosher by the Orthodox Union and Halal by the Islamic Food Council of Europe.

ANDEROL® Food Grade Lubricants meet the requirement of the FDA regulation 21 CFR 178.3570.

PROPERTIES	TEST METHOD	ANDEROL PQAA 150
Appearance @ 20°C	visual	Clear yellow liquid
Viscosity @ 40°C, cSt	ASTM D-445	158
Viscosity @ 100°C, cSt	ASTM D-445	16.3
Viscosity Index	ASTM D-2270	108
Density @ 15°C, kg/l	ASTM D-1298	0.862
Total Acid Number, mg KOH/g	ASTM D-664	1.3
Flash Point, COC, °C	ASTM D-92	217
Pour Point, °C	ASTM D-97	-15
Demulsibility @ 54°C	ASTM D-1401	15
4-Ball Wear, 1200 rpm, 75°C, 40 kg	ASTM D-4172	0.4
4-Ball Weld, kg	ASTM D-2783	126

FOR MORE INFORMATION PLEASE REFER TO THE RELEVANT MATERIAL SAFETY DATA SHEET

REGISTRATIONS



ANDEROL®
Specialty Lubricants

Groot Egtenrayseweg 23, 5928 PA Venlo, The Netherlands • Tel: +31 (0)77 3960340 • www.anderol-europe.com

This information is furnished without warranty, representation, inducement, or license of any kind except that it is accurate to the best of OUR knowledge or obtained from sources believed by ANDEROL® to be accurate. ANDEROL® does not assume any legal responsibility for use of reliance upon it. Only Chemists or chemically qualified lab technicians should carry out tests. Before using any chemicals, read its label and Material Safety Data Sheet.