

DESCRIPTION

- **LubeRite ATF III** is a multifunctional fluid for automatic and power-shift transmissions. It is designed to meet the tropical country requirements of General Motors Dexron III, Ford Mercon, Allison C-4, and Caterpillar TO-2.

PROPERTIES

- Provides quiet operation and smooth shifting.
- Resistant to high temperature oxidation and fluid thickening.
- Controlled Frictional properties.
- Outstanding anti-wear performance.
- Protects against harmful attack by corrosive acids.
- Provides protection against rusting and corrosion.
- Compatibility with commonly used seal materials.
- Outstanding hydraulic pump performance.

TYPICAL CHARACTERISTICS

Specific Gravity at 15.6 °C	0.8768
Color, Visual	Red
Viscosity at 40°C, cSt	38.5
Viscosity at 100°C, cSt	7.4
Viscosity Index	161
Flash Point, COC, °C	196

APPLICATIONS

- Automatic transmissions, power steering, hydraulic systems, torque converters in cars, trucks and heavy equipment.
- For gearboxes fo front-wheel drive cars.
- Suitable for use in applications where fluids meeting Dexron III, Mercon, Allison C-4 or Caterpillar TO-2 performance are recommended.

GRADE

- SAE 20

AVAILABLE PACKAGING

- 210-liter drum
- 20-liter pail