

DESCRIPTION

- **LubeRite DEO 40 CF** is a high performance, single-grade engine oil designed to meet the requirements of turbocharged and supercharged automotive diesel engines, especially those used in passenger cars and buses.

PROPERTIES

- Provides better protection against acids and bearing weight loss.
- Has low levels of camshaft and valve train wear.
- Possesses outstanding sludge, deposit and gum control capabilities.

GRADES

- SAE 10, 30, and 40

APPLICATIONS

- Designed for a wide range of automotive diesel and gasoline-powered engines, such as heavy-duty highway vehicles not requiring a multigrade oil.
- Can also be used as hydraulic and transmission oil for forklifts and construction equipment.

QUALITY LEVELS

- API Service CF/SF
- Mercedes Benz p227.0

AVAILABLE PACKAGING

- 200-liter drum
- 20-liter pail

TYPICAL CHARACTERISTICS

	10	30	40
Specific Gravity at 15.6 °C	0.8697	0.8910	0.8955
Flash Point, COC, °C	218	236	248
Viscosity at 40°C, cSt	30.4	95.3	137.9
Viscosity at 100°C, cSt	5.30	11.20	14.50
Viscosity Index	104	104	104
TBN (mgKOH/g)	10.1	10.1	10.1