

DESCRIPTION

LubeRite GEO 20W50 with high temperature stabilization additive is a high-quality, multi-grade gasoline engine oil designed to meet the high performance requirements of most modern vehicles.

The high temperature stabilization additive keeps the oil stable even at extreme temperatures, providing ultimate protection from engine stress.

PROPERTIES

- Gives superior anti-wear protection to cylinder rings, linear and valve trains
- Keeps engine clean through superior control of sludge, rust, deposits, gums and resins
- Cost effective due to fuel economy and extended oil drain characteristics

APPLICATION

- Gasoline-powered cars/trucks, high-speed automotive engines.

QUALITY LEVELS

- API Service SL
- CCMC G4 (90)/PD-2
- Volkswagen 501/505
- MB p229.1
- ACEA A2-96, A3-98, B2-98, B3-98

TYPE

- Multi-grade Gasoline Engine Oil

GRADE

- SAE 20W-50

AVAILABLE PACKAGING

- 20-liter pails and 200-liter drums.

TYPICAL CHARACTERISTICS

Specific Gravity at 15.6°C	0.8850
Flash Point, COC, °C	226
Color, ASTM	3.5
Kinematic Viscosity at 40°C, cSt	179.3
Kinematic Viscosity at 100°C, cSt	19.61
Viscosity Index	126
TBN (mg KOH/g)	6.7