

DRAWLUB S 15

MULTIFUNCTIONAL METALFORMING OIL

DRAWLUB S 15 is a mineral oil free, water immiscible coolant especially for chip less metal forming operations on steel and nonferrous metals like aluminium and copper.

DRAWLUB S 15 can be used as a multi-purpose coolant, providing excellent lubrication properties. Therefore, the product is especially suitable for difficult metal forming operations (fine-blanking, bending, deep drawing), but can also be applied in the field of machining operation (drilling, sawing, milling).

DRAWLUB S 15 Benefits:

- Suitable for wide range of metals and processes
- Low odour, high flash point formulation for pleasant working conditions
- Environment-friendly, German-WGK 1, free from mineral oil

Residual films on DRAWLUB S 15 can easily be removed by using conventional cleaners.

Physical data

Appearance		light brown, low viscosity fluid	
Density/20 °C	DIN 51757	approx. 0.901	g/cm ³
Viscosity/40 °C	DIN 51562/1	approx. 13	mm ² /s
Flash point	ISO 2 592	> 180	°C
Copper Corrosion	ASTM D130	1a	

Handling and Storage:

DRAWLUB S 15 should not be exposed to extremes of temperature. The product should have ambient temperature before use.

Only valid in combination with EC-Safety-Data-Sheet.

Warranty

The information given here is considered to be correct and is offered for your consideration, investigation and verification. No warranties are expressed or implied since the use of our products is beyond our control. Statements concerning the use of PETROFER-products are not to be constructed as recommending the infringement of any patent.