

TAPPING COMPOUNDS & FLUIDS

For hand-applied machining, especially for tapping, reaming and drilling, Syntech Procut Liquid and Compound reduces the frictional forces in the cutting process, and reduces temperatures. In effect, tool life is prolonged, while surface finish is at an optimum. The products are safe for non-ferrous metals and especially formulated for hard steels including Stainless Steels and Inconel. Apply on the cutting tool by brush or dipping.



In 400 ml bottle

DRY MOLY SPRAY

Syntech's Dry Moly spray is a black, solid, dry, tenacious and wear-resistant film sprayed into plain bearings, guides, chutes, pins, cams, slides, ejector pins and other applications wherein fluid oils and greases are not applicable. It may be used in temperatures up to 450°C, and prevents the pick-up of contaminants. May also be used as an anti-seize agent.



In 400 ml cans

DRY TEFLON SPRAY

Syntech's Dry PTFE Spray is a white, solid, dry, tenacious and non-toxic film sprayed into guides, chutes, pins, cams and slides. Usable for temperatures of up to 270°C, use the Dry PTFE ensures a clean, non-stick lubricating condition at all times.



In 400 ml cans

ANTI-SEIZE PASTE

Tacbecon's S1100 is a paste with fine copper particles applied on threaded components such as large bolts and nuts to prevent seizure, stress-cracking, and corrosion. It also reduces dismantling torque significantly, prolonging the life of machine components. Apply on the threaded assembly after cleaning, by brush. May be used up to 1,000°C



In 500 gram jars

LUBRICATING AND MAINTENANCE AIDS

Due to years of in-depth interaction with the end-users from various industries in the Philippines, Fluid Solutions, Inc. (FSI) developed a full range of Handy Lubricating Solutions for the maintenance practitioners. These products were formulated together with the global leaders in lubricant technology.

fluid
SOLUTIONS
Everything Runs Smoothly

Unit 812 AIC Burgundy Empire Tower,
ADB Avenue Cor. Sapphire and Garnet
Roads, Ortigas, Pasig
Tel Nos.: (02) 696-7120 or (049) 541-1734
Fax Nos.: (02) 696-7121 or (049) 541-0447
Email: fluidsolutions@rocfi.com.ph
Website: www.fluidsolutions.com.ph

Also Available:

SPECIALTY LUBRICANTS AND GREASES

High and Low Temperature Greases
Chain and Wire Rope Lubricants
Open Gear Greases
Synthetic Gear, Compressor, Hydraulic Oils
Fire Resistant Hydraulic Fluids

METALWORKING FLUIDS

Die Casting, Forging, Stamping
Release Agents
Rust Preventives and VCI's
Cutting Oils, and Coolants,
Anti Rust

AUTOMATIC LUBRICATORS

OIL SKIMMERS

fluid
SOLUTIONS
Everything Runs Smoothly

MULTI-PURPOSE OIL SPRAY / PENETRATING OILS

The Loctite ML-11 is formulated as a Penetrating Oil, Rust Inhibitor, Dewatering Agent and All-around Lubricant. With a mild cherry scent, the Loctite ML-11 may be used without detrimental effect to all metals, plastics, and rubbers.

In 360 ml spray cans



SAFETY ELECTRICAL CONTACT CLEANER

The Loctite 7039 is an Electrical & Electronics Contact Cleaner that does not affect any components and varnishes. It is quick-drying in nature, and removes moisture and contamination on electrical and electronic contacts. It may be in applications up to 50°C, and importantly, it leaves an invisible and undetectable film that repels water for protection.

In 400 ml spray cans



FOOD GRADE HIGH PERFORMANCE SPRAY OIL

The Syntech Food Multi-Spray is an NSF H1 rated Lubricant for use in chains, links, pins, pivots, small bearings and other metal components that may have incidental contact with food stuffs. It may also be used as a Penetrating Oil, Rust Preventive and a Dewatering Agent. Fully synthetic in nature, it is highly resistant to water and may be applied to temperatures of up to 270°C.

In 400 ml cans



RUST PROTECTION SPRAY

Moisture Gard C is a thin colorless film suitable for medium/long term indoor protection of components such as bearings, gears, pressings and any machined metal product which requires protection from corrosion - whether in storage, transit, or between operations.

Also available in green thin film, Syntech Moisture Gard Green



SILICONE MOULD RELEASE AGENT

Syntech Silicone Spray provides a fast, efficient, and clean release in complex moulding operations, especially on plastics. The silicone oil in the formulation ensures a wet film even at 200°C, and a glossy finish is typically achieved. Difficulties at start-up are minimized using Silicone Mould Release Agent.

Available in 400 ml cans



HEAVY DUTY DEGREASER

The Syntech HD Degreaser cuts through oils, grease, grime, sludges, waxes and other deposits that are difficult to wash off by conventional methods. Simply spray on the surfaces affected, and allow the fluid to soak for a few minutes before wiping or washing off the contaminants with water. For heavier contamination, allow the fluid to soak for a longer duration. Safe for all substrates.

In 400 ml cans



NON-SILICONE MOULD RELEASE AGENT

Syntech Non-Silicone Spray is for use when silicone or PTFE based fluids are not preferred in the moulding process. Recommended for plastic or rubber molded parts that undergo printing or painting in the subsequent process. Non-Silicone Mould Release Agent produces a wet film that resists temperatures of up to 150°C, and is highly helpful for applications using Polypropylene, Expanded Polystyrene, Nylon A100 and Nitrile Rubbers.

Available in 400 ml cans



HIGH PERFORMANCE SPRAY GREASE

Syntech's Ruby Spray Grease is a Lithium Complex Grease fortified with PTFE in order to withstand high temperatures and extreme loads. It does not leave sticky or gummy residues, and provides excellent corrosion protection. Use at temperatures of up to 220°C and up to speed factors of 750,000.

In 360 ml spray cans

