

DESCRIPTION

LubeRite HDG GL5 is the highest quality general purpose type gear lubricant suitable for heavy loads sustained at high speeds and subjected to high torque.

PROPERTY

- Multigrades meet both low and high temperature requirements.

GRADES

- Monogrades – SAE 90 and 140
- Multigrades – 80W 90 and 85W 140

QUALITY LEVELS

- API Service GL-5
- MIL-L-2105D

APPLICATIONS

- Hypoid or spiral-bevel gears, limited-slip differentials and transmissions.
- Fortified with extreme pressure additives, it is used in certain hypoid or spiral-bevel gears, transmissions or gear boxes and limited-slip differentials of both highway and off-highway vehicles.

AVAILABLE PACKAGING

- 200-liter drum
- 20-liter pail

TYPICAL CHARACTERISTICS

	80W/90	85W/140	90	140
Specific Gravity at 15.6 °C	0.8991	0.9095	0.9076	0.9171
Flash Point, COC, °C	210	220	210	226
Color, ASTM	3.5	4.5	7.0	7.5
Viscosity at 40 °C, cSt	133.5	345.6	203.8	488.7
Viscosity at 100 °C, cSt	13.88	25.40	17.52	30.40
Viscosity Index	100	96	92	91